

FLOOR HEATING MAT (FHM-SX-100)



- Heating Cable of 10 w/m
- XLPE Insulation on heating core
- Al Foil Shield With Solid Earth Wire
- Sticky FG Mesh/Non-Sticky FG Mesh/Cross Filament Tape
- Double sided tissue tape / PP tape
- PVC Outer Jacket (Heat Resistance)
- Separate Cold Tail of 3.5 meter.

Construction

Heating Cable	10 watt / meter
Spacing	Sticky FG Mesh/ Non-Sticky FG Mesh/ Cross Filament Tape
Core Insulation	XLPE
Shielding	Aluminium Foil For 100% Coverage
Earth Wire	TPC 1.0mm (Solid)
Jacket	PVC (HR FR)
Power Output per Meter ²	100 Watt / Meter ²
Standard Voltage	230 Volt AC

Range

Model	Watts	Mat Area (Meter ²)
FHM-SX-100-100	100	1.0
FHM-SX-100-200	200	2.0
FHM-SX-100-300	300	3.0
FHM-SX-100-400	400	4.0
FHM-SX-100-500	500	5.0
FHM-SX-100-600	600	6.0
FHM-SX-100-800	800	8.0
FHM-SX-100-1000	1000	10.0
FHM-SX-100-1200	1200	12.0
FHM-SX-100-1500	1500	15.0
FHM-SX-100-1900	1900	19.0