

## TEMPMET 08

### Input

**Thermocouples:** J, K, N, E, R, S, T, B, C, D

**RTD** : Pt100, Pt10, Pt1000, Pt50, Pt200, Pt500

**Unit** : °C, °F

**Resolution** : 0.01°C

**Accuracy** : 0.1% of full scale

**Channel** : Tempmet 08-02 : 1 T/C, 1 RTD  
Tempmet 08-04 : 2 T/C, 2 RTD

## TEMPMET 08



### Specification

RTD + T/C Type	RTD + T/C Range	Accuracy
		Tempmet 08
Pt100	-200°C to 850°C	±1.05°C
Pt10	-200°C to 800°C	±1.0°C
Pt1000	-200°C to 800°C	±1.0°C
Pt 50	-200°C to 800°C	±1.0°C
Pt200	-200°C to 800°C	±1.0°C
Pt500	-200°C to 800°C	±1.0°C
J	-210°C to 1200°C	±1.41°C
K	-200°C to 1372°C	±1.57°C
N	-200°C to 1300°C	±1.50°C
E	-200°C to 1000°C	±1.20°C
R	0°C to 1768°C	±1.76°C
S	0°C to 1768°C	±1.76°C
T	-200°C to 400°C	±0.65°C
B	400°C to 1820°C	±1.42°C
C	0°C to 2315°C	±2.315°C
D	0°C to 2315°C	±2.315°C