

SFEP-101

EXTRUDED

(FEP) INSULATED SLEEVE 200°C



FEATURES

- ✓ Max. Temp. Up to 200°C
- ✓ Excellent Heat Resistant
- ✓ Excellent Dielectric Property
- ✓ Excellent Chemical Resistant
- ✓ Non Stick Property
- ✓ Weather Resistant
- ✓ Flame Retardant
- ✓ Good Thermal Stability

AVAILABLE OPTIONS

- ✓ Available in Different Color
- ✓ Available with different wall thickness as well as voltage Grade.

EXTRUDED FEP INSULATED SLEEVE

S.No.	Size in (mm)	Inner Dia (mm)	Wall Thickness (mm)	Max. Outer Dia (in mm)	Approx Weight (gm/mtr)
SFEP101	1	1	0.2	1.4	1.8
SFEP102	1.2	1.2	0.2	1.6	2.1
SFEP103	1.4	1.4	0.25	1.9	3.1
SFEP104	1.5	1.5	0.3	2.1	4
SFEP105	1.6	1.6	0.3	2.2	4.3
SFEP106	1.75	1.75	0.35	2.45	5.3
SFEP107	2	2	0.35	2.7	5.9
SFEP108	2.5	2.5	0.35	3.2	7.1
SFEP109	4	4	0.4	4.8	12.5

ORDERING CODE

Conductor Size

(SFEPXXX)

101
to
109

Color Code

(XX)

RE
YE
BR
BL
BK
GR
PU
OR
WH
GN

Note : RE - (Red), YE - (Yellow), BR - (Brown), BL - (Blue), BK - (Black), GR - (Grey), PU - (Purple), OR - (Orange), WH - (White), GN - (Green)