

# SFIB-101

## BRAIDED

### FIBER GLASS INSULATED SLEEVE 400°C



#### FEATURES

- ✓ Max. Temp. Up to 400°C
- ✓ Excellent Heat Resistant.
- ✓ Excellent Flexibility.
- ✓ Silicon Insulated Varnish at outer.
- ✓ Good Strength.
- ✓ Resist against many solvent, oils, and concentrated acids.
- ✓ Outstanding Electrical Properties

#### AVAILABLE OPTIONS

- ✓ Available in White & Black Color
- ✓ Available with different wall thickness as well as voltage Grade.

### BRAIDED FIBRE GLASS INSULATED SLEEVE

S.No.	Size in (mm)	Inner Dia (mm)	Wall Thickness (mm)	Max. Outer Dia (in mm)	Approx Weight (gm/mtr)
SFIB101	1.5	1.5	0.20	1.90	3.00
SFIB102	2.0	5	0.30	2.60	5.00
SFIB103	3.0	3.0	0.35	3.70	7.50
SFIB104	6.0	6.0	0.40	6.80	15.00
SFIB105	12.0	12.0	0.60	13.20	40.00
SFIB106	15.0	15.0	0.60	16.20	48.00
SFIB107	16.0	16.0	0.65	17.30	52.00
SFIB108	26.0	26.0	0.80	27.60	92.00
SFIB109	30.0	30.0	0.90	31.80	110.00

#### ORDERING CODE

Conductor Size

(SFIBXXX)

101  
to  
109

Color Code

(XX)

BK  
WH

**Note :** BK - (Black), WH - (White)