

STEF-101

WRAPPED

PTFE INSULATED SLEEVE 260°C



FEATURES

- ✓ Max. Temp. Up to 260°C
- ✓ Excellent Heat Resistant..
- ✓ Excellent Chemical Resistant
- ✓ Non Stick Property.
- ✓ Weather Resistant.
- ✓ Good Thermal Stability

AVAILABLE OPTIONS

- ✓ Available in Different Color
- ✓ Available with different wall thickness as well as voltage Grade.

WRAPPED PTFE INSULATED SLEEVE

S.No.	Size in (mm)	Inner Dia (mm)	Wall Thickness (mm)	Max. Outer Dia (in mm)	Approx Weight (gm/mtr)
STEF101	1	1	0.2	1.4	1.8
STEF102	1.2	1.2	0.2	1.6	2.1
STEF103	1.4	1.4	0.25	1.9	3.1
STEF104	1.5	1.5	0.3	2.1	4
STEF105	1.6	1.6	0.3	2.2	4.3
STEF106	1.75	1.75	0.35	2.45	5.3
STEF107	2	2	0.35	2.7	5.9
STEF108	2.5	2.5	0.35	3.2	7.1
STEF109	4	4	0.4	4.8	12.5
STEF110	6	6	0.45	6.9	20.4
STEF111	8	8	0.5	9	30.2

ORDERING CODE

Conductor Size

(STEFXXX)

101
to
111

Color Code

(XX)

RE
YE
BR
BL
BK
GR
PU
OR
WH
GN

Note : RE - (Red), YE - (Yellow), BR - (Brown), BL - (Blue), BK - (Black), GR - (Grey), PU - (Purple), OR - (Orange), WH - (White), GN - (Green)